

Technical Specifications for Acrymica Laminates

Num	Attributes	Units	High Gloss	Supermatt
1	Thickness	mm	1.5	1.4
2	Thickness Variation	mm	±0.2	±0.2
3	Mean Length	mm	2440	2440
4	Length Variation	mm	±5.0	±5.0
5	Mean Width	mm	1220	1220
6	Width Variation	mm	±5.0	±5.0
7	Gloss Level	DIN 67 530 (60 Degrees), GLE	>90%	<8%
8	Scratch Resistance	IHD-W-466, Method A	1.1 N	>2 N
9	Resistance to Steel Wool	Load: 1kg, Strokes: 20, Steel Wool Type: 00	Class 1, No changes or visible scratches	Class 1. No changes or scratches visible
10	Color Fastness	EN ISO 4892-2	DE <1.7	DE <1.7
11	Anti-finger Print		-	Yes
12	Anti-bacterial		-	Yes
13	Surface Protection		A protective PE film	A protective PE film
14	Edgeband Material		ABS	ABS
15	Edgeband Thickness	mm	1	1
16	Edgeband Width	mm	23/45	23/45

Note:

- 1 The values for respective attributes are listed based on the data received from the suppliers for the respective material
- 2 Specifications and materials of the products are subject to change without notice
- 3 Our liability is limited to our product only